

## CW1128 Voice Cable

CW1128 External telephone cables are suitable for installation outdoors where an armoured cable is not necessary. They offer a light-weight, compact, tough solution for cables that will have to endure a variety of weather conditions, from rain and snow to bright sunlight. CW1128 is ideal for clipping around the outside of buildings or running through ducting. The outer sheath is made from tough, durable Polyethylene which is also UV and sunlight re-sistant. The pairs are bedded in Petroleum Jelly to protect against the ingress of moisture.

Solid plain copper conductor, colour coded Polyethylene insulation, Petroleum Jelly filled, separator tape and a Black Polyethylene sheath.



### Technical Specifications

Max Conductor @ 20°C - ohms/KM	91
Min insulation resistance @ 20°C - megaohms/KM	1500
Average mutual capacitance nanoFarads/KM	56
Conductor Diameter - mm	0.5
Conductor Size - sqmm	0.2
Radial Thickness of insulation - mm	0.2
Nominal Diameter of core - mm	0.9
Temperature Rating	0°C to +40°C
Minimum Bending Radius	10 x OD

Part Number	Description
NC-CW1128-10	10 PAIR EXTERNAL CABLE POLY BLACK
NC-CW1128-20	20 PAIR EXTERNAL CABLE POLY BLACK
NC-CW1128-25	25 PAIR EXTERNAL CABLE POLY BLACK
NC-CW1128-50	50 PAIR EXTERNAL CABLE POLY BLACK
NC-CW1128-100	100 PAIR EXTERNAL CABLE POLY BLACK