

CW-1308B Voice Cable

Telephone cable to standard BT specification suitable for use externally and within buildings. As standard it is available from 10pair to 320 pair and is normally supplied with a 1.38mm cream earth wire as standard. The sheath is black LSZH and has the addition of an Aluminium/Polyethylene laminate tape which is bonded to the sheath. This provides an effective moisture barrier. The cables are metre marked for ease of use during installation.



Technical Specifications

Standards	CW1308 - IEC 60754-1
Conductor	Class 1 solid annealed plain copper
Insulation	PVC (Polyvinyl Chloride)
Separator	Polyester wrapping tape
Screen	Al/PE (Aluminium/Polyethylene) tape
Sheath	LSZH (Low Smoke Zero Halogen)
Colour	Black
Temperature Rating	0°C to +70°C
Minimum Bending Radius	15 x overall diameter

Part Number	Description
NC-CW1308B-10E	10 PAIR + E INTERNAL/EXTERNAL CABLE LSF BLACK
NC-CW1308B-20E	20 PAIR + E INTERNAL/EXTERNAL CABLE LSF BLACK
NC-CW1308B-50E	50 PAIR + E INTERNAL/EXTERNAL CABLE LSF BLACK
NC-CW1308B-100E	100 PAIR + E INTERNAL/EXTERNAL CABLE LSF BLACK
NC-CW1308B-200E	200 PAIR + E INTERNAL/EXTERNAL CABLE LSF BLACK
NC-CW1308B-320E	320 PAIR + E INTERNAL/EXTERNAL CABLE LSF BLACK