## Net-C FC Adaptors MM/SM









FC Singlemode ADAPTOR



FC/APC ADAPTOR

- Low insertion loss.
- Easy to handle.
- Environmentally stable.
- Compliant with IEC, TIA.
- Hybrid adaptors available.

## Applications:

- Local Area Networks.
- FTTH (Fibre To The Home).
- CATV and CCTV.
- Telecoms.

Mode	Singlemode	Multimode
Typical Insertion loss	0.20dB	0.30dB
Humidity Cycling	75°C RH 95%	75°C RH 95%
Vibration	10-55 hz (3 axis)	10-55 hz (3 axis)
Durability ( 500 matings)	0.12 dB Max	0.12 dB Max

Part Number	Description	
AD-FC-MM	FC simplex Multimode adaptor	
AD-FC-SM	FC simplex Singlemode adaptor	
AD-FCA-SM	FC/APC simplex Singlemode adaptor	

- » D Shape as standard.
- D shape easily installs into patch panels.
- » Available in square and rectangular mount.
- Metal body for long life and more than 1000 matings.
- >> Multimode phosphor bronze and Singlemode ceramic sleeves.
- Meet JIS5970 and Bellcore GR-326 standard



Call: +44 (0) 1403 754 233, Email: enquiries@networkscentre.com or visit: www.networkscentre.com Networks Centre ltd, Head Office, Lawson Hunt Industrial Park, Broadbridge Heath, West Sussex, RH12 3JR