

Net-C ST Adaptors MM/SM



**ST Multimode
SIMPLEX ADAPTOR**



**ST Singlemode
SIMPLEX ADAPTOR**

- » Low insertion loss.
- » Easy to handle.
- » Environmentally stable.
- » Compliant with IEC, TIA.
- » Hybrid adaptors available.

Applications:

- » Local Area Networks.
- » FTTH (Fibre To The Home).
- » CATV and CCTV.
- » Telecoms.

Mode	Singlemode	Multimode
Typical Insertion loss	0.20dB	0.30dB
Humidity Cycling	75°C RH 95%	75°C RH 95%
Vibration	10-55 hz (3 axis)	10-55 hz (3 axis)
Durability (500 matings)	0.12 dB Max	0.12 dB Max

Part Number	Description
AD-ST-MM	ST simplex Multimode adaptor
AD-ST-SM	ST simplex Singlemode adaptor
AD-STA-MM	ST/APC simplex Singlemode adaptor
AD-STA-SM	ST/APC simplex Multimode adaptor

- » D shape as standard.
- » D shape threaded with nuts easily installs into patch panels.
- » Meets Bellcore GR326 and TIA 568A standard.
- » Zinc alloy coupling body for long life.
- » Available in a plastic or metal duplex with SC duplex footprint.
- » Available in a plastic or metal simplex with SC simplex footprint.

